

QC-TRI PRO-2.5 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 254 Watts / Low: 196 Watts
Air Flow	Hi: 2304 CFM / Low: 1923 CFM
HVI-916 Airflow	1991 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 1150 SQ FT
# of Speeds	2
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	3.1 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 18 1/4"
Removable Grille Outside Dimension	16" x 20"
Shipping Weight	43 lbs.
Box Dimensions	38" x 20" x 24"
In The Box	<ul style="list-style-type: none"> -QC TRI PRO-2.5 Motorhead -Removable Grille -Cut-out Template -Window Lock -Damper Box -6 Foot Duct -Accessory Bag -Controls

