

### QC-TRI PRO-4.8 Specifications

Motor Voltage	120 VAC, 60 Hz								
Energy Use	Hi: 673 Watts / Low: 494 Watts								
Air Flow	Hi: 4740 CFM / Low: 3438 CFM								
HVI-916 Airflow	3750 CFM								
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 2350 SQ FT								
# of Speeds	2								
Duct Diameter	18"								
Duct Length	9 feet								
Motor Head Diameter	18 1/2"								
Motor Head Length	13 1/2"								
Dampers	Barometric Pressurized R5 Dampers								
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch								
Warranty	15 Years								
Framing	None Required								
Joist Cutting	None Required; fits 16" or 24" on center								
Minimum Suggested Attic Venting	6.3 SQ FT net free area								
Ceiling Rough Opening	14 1/4" x 30 1/4"								
Removable Grille Outside Dimension	16" x 32"								
Shipping Weight	64 lbs.								
Box Dimensions	40" x 22" x 36"								
In The Box	<table border="0"> <tr> <td>-QC TRI PRO-4.8 Motorhead</td> <td>-Damper Box</td> </tr> <tr> <td>-Removable Grille</td> <td>-9 Foot Duct</td> </tr> <tr> <td>-Cut-out Template</td> <td>-Accessory Bag</td> </tr> <tr> <td>-Window Locks</td> <td>-Controls</td> </tr> </table>	-QC TRI PRO-4.8 Motorhead	-Damper Box	-Removable Grille	-9 Foot Duct	-Cut-out Template	-Accessory Bag	-Window Locks	-Controls
-QC TRI PRO-4.8 Motorhead	-Damper Box								
-Removable Grille	-9 Foot Duct								
-Cut-out Template	-Accessory Bag								
-Window Locks	-Controls								



QC-TRI PRO-4.8  
QuietCool Trident Pro Line