



QC-TRI PRO-6.5 Specifications

120 VAC, 60 Hz	
Hi/Hi: 855 Watts / Hi/Lo: 590 Watts	
Hi/Off: 309 Watts / Lo/Off: 271 Watts	
Hi: 6123 CFM / Hi/Lo: 5646 CFM	
Hi/Off: 3400 CFM / Low/Off:	2875 CFM
5398 CFM	
Covers up to 3050 SQ FT	
4	
16"	
6 feet	
16 1/2"	
13 1/2"	
Barometric Pressurized R5 Dampers	
Included 8 Hour Electronic Timer and Double	
3-Way Switch	
15 Years	
None Required	
None Required; fits 16" or 24" on center	
8.2 SQ FT net free area	
14 1/4" x 36 1/4"	
16" x 38"	
87 lbs.	
42" × 20" × 38"	
-QC TRI PRO-6.5 Motorhead	-Damper Box
-Removable Grille	-6 Foot Duct(2)
-Cut-out Template	-Accessory Bag(2)
-Window Locks	-Controls
	Hi/Hi: 855 Watts / Hi/Lo: 590 Hi/Off: 309 Watts / Lo/Off: 27 Hi: 6123 CFM / Hi/Lo: 5646 C Hi/Off: 3400 CFM / Low/Off: 5398 CFM Covers up to 3050 SQ FT 4 16" 6 feet 16 1/2" 13 1/2" Barometric Pressurized R5 D Included 8 Hour Electronic Ti 3-Way Switch 15 Years None Required None Required None Required; fits 16" or 24 8.2 SQ FT net free area 14 1/4" x 36 1/4" 16" x 38" 87 lbs. 42" x 20" x 38" -QC TRI PRO-6.5 Motorhead -Removable Grille -Cut-out Template

