

### QC-TRI PRO-3.3 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 318 Watts / Low: 258 Watts
Air Flow	Hi: 3118 CFM / Low: 2766 CFM
HVI-916 Airflow	2809 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 1550 SQ FT
# of Speeds	2
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	4.2 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 22 1/4"
Removable Grille Outside Dimension	16" x 24"
Shipping Weight	47 lbs.
Box Dimensions	38" x 20" x 27"
In The Box	<ul style="list-style-type: none"> <li>-QC STL PRO-3.3 Motorhead</li> <li>-Removable Grille</li> <li>-Cut-out Template</li> <li>-Window Locks</li> <li>-Damper Box</li> <li>-6 Foot Duct</li> <li>-Accessory Bag</li> <li>-Controls</li> </ul>

