

### QC-TRI PRO-5.5 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 778 Watts / Low: 512 Watts
Air Flow	Hi: 5614 CFM / Low: 3350 CFM
HVI-916 Airflow	4461 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 2800 SQ FT
# of Speeds	2
Duct Diameter	20"
Duct Length	9 feet
Motor Head Diameter	20 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	7.5 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	76 lbs.
Box Dimensions	42" x 24" x 38"
In The Box	<ul style="list-style-type: none"> <li>-QC TRI PRO-5.5 Motorhead</li> <li>-Removable Grille</li> <li>-Cut-out Template</li> <li>-Window Locks</li> <li>-Damper Box</li> <li>-9 Foot Duct</li> <li>-Accessory Bag</li> <li>-Controls</li> </ul>



QC-TRI PRO-5.5  
QuietCool Trident Pro Line